INDEX TO VOLUME 34 1999

Index to Authors and Contributors

ALIABADI, M. H. *Papers* Evaluation of the stress intensity factors for a three-dimensional interfacial crack by the boundary element method, 209. Dual boundary element methods for three-dimensional dynamic crack problems, 373
ALEXANDROV, S. *Paper* Disc upsetting between spherical dies and its application to the determination of forming limit curves, 17
AREF, B. *Paper* Film data reduction from Taylor impact tests, 337
ATZORI, B. *Paper* Stress field parameters to predict the fatigue strength of notched components, 437

BATISTA, M. *Technical Note* Stresses in a confocal elliptic ring subject to uniform pressure, 217
BAEK, T. H. *Paper* Experimental determination of stress concentrations in orthotropic composites, 69
BECKER, A. A. *Paper* A quadratic boundary element formulation for three-dimensional contact problems with friction, 235
BONORA, N. *Paper* Identification and measurement of ductile damage parameters, 463
BROOKFIELD, D. J. *Paper* Material properties from small specimens using the punch and bulge test, 423

CARLTON, A. *Paper* Material properties from small specimens using the punch and bulge test, 423
CHEUNG, J. S. T. *Paper* Horizontal vessels on fixed supports used for storing high-temperature liquid: an experimental validation of finite element modelling, 83
CHIKANOVA, N. *Paper* Disc upsetting between spherical dies and its application to the determination of forming limit curves, 17
CIAVARELLA, M. *Technical Note* The design of hydrodynamically lubricated journal bearings against yield, 165
COLLINS, R. A. *Paper* Ensuring the continued structural airworthiness of the Airbus A300 commercial transport aircraft, 413
COVA, P. *Paper* Accelerated life testing and thermomechanical simulation in power electronic device development, 455
CRISTOFOLINI, L. *Paper* Towards the standardization of *in vitro* load transfer investigations of hip prostheses, 1
CROCOMBE, A. *Paper* Finite element modelling of local contact conditions in gear teeth, 129

DABNICHKI, P. *Paper* Finite element modelling of local contact conditions in gear teeth, 129
DECUZZI, P. *Technical Note* The design of hydrodynamically lubricated journal bearings against yield, 165
DEMELIO, G. *Technical Note* The design of hydrodynamically lubricated journal bearings against yield, 165
DUMANSKY, A. M. *Technical Note* Creep and relaxation of heritable orthotropic continua under the plane stress state, 361

FESSLER, H. *Paper* Advantages of cylindrical keys for torque transmission, 225
FOSTER Jr, J. C. *Paper* Film data reduction from Taylor impact tests, 337

GILLIS, P. P. *Paper* Film data reduction from Taylor impact tests, 337
GOWHARI-ANARAKI, A. R. *Technical Note* Equivalent stress and total strain range predictions for multiaxial states of stress and strain, 53
GRANT, R. J. *Papers* Crack growth in pin-loaded tubes. Part 1: numerical analysis, 253. Crack growth in pin-loaded tubes. Part 2: comparison of experimental data with numerical results, 271

HARDY, S. J. *Technical Note* Equivalent stress and total strain range predictions for multiaxial states of stress and strain, 53
HELLEN, T. K. *Paper* Material properties from small specimens using the punch and bulge test, 423
HELLER, M. *Paper* A gradientless finite element procedure for shape optimization, 323
HENSHALL, J. L. *Paper* The analysis of termination effects in wire strand using the finite element method, 31
HILLS, D. A. *Papers* A shrink-fit peg subject to bending and shearing forces, 23. Origins of partial slip in fretting—a review of known and potential solutions, 175. *Technical Note* The design of hydrodynamically lubricated journal bearings against yield, 165
HOBBS, R. E. *Papers* Axial stiffness and torsional effects in a 76 mm wire rope: experimental data and theoretical predictions, 39. Stress intensity factors for a semi-elliptical surface crack in a T-shaped geometry. Part 1: tension and bending results, 147. Stress intensity factors for a semi-elliptical surface crack in a T-shaped geometry. Part 2: approximate solutions at the deepest point for arbitrary crack-face loading, 157
HOUSE, J. W. *Paper* Film data reduction from Taylor impact tests, 337
HOWARD-HILDIGE, R. *Paper* Material properties from small specimens using the punch and bulge test, 423
HUANG, Y.-Q. *Paper* Bimaterial interface hybrid element for piezoelectric laminated analysis, 97
HYDE, T. H. *Paper* An experimental and finite element study of the non-linear force–displacement characteristics of tubular YT-joints under combined axial loading, 183

JARVIS, J. *Paper* Material properties from small specimens using the punch and bulge test, 423
JIANG, W. G. *Paper* The analysis of termination effects in wire strand using the finite element method, 31

KAYE, R. *Paper* A gradientless finite element procedure for shape optimization, 323
KRAINCANIC, I. *Paper* Axial stiffness and torsional effects in a 76 mm wire rope: experimental data and theoretical predictions, 39

LANCASTER, E. R. *Paper* Stress intensity factors for a semi-elliptical surface crack in a T-shaped geometry. Part 1: tension and bending results, 147
LAZZARIN, P. *Paper* Stress field parameters to predict the fatigue strength of notched components, 437
LEAHY, J. G. *Paper* A quadratic boundary element formulation for three-dimensional contact problems with friction, 235
LEEN, S. B. *Paper* An experimental and finite element study of the non-linear force–displacement characteristics of tubular YT-joints under combined axial loading, 183
LEEVERS, P. S. *Papers* Non-uniform and dynamic torsion of elastic beams. Part 1: governing equations and particular solutions, 303. Non-uniform and dynamic torsion of elastic beams. Part 2: the double torsion test, 313
LI, W. *Paper* Material properties from small specimens using the punch and bulge test, 423
LING, Z. *Paper* Horizontal vessels on fixed supports used for storing high-temperature liquid: an experimental validation of finite element modelling, 83
LIU, M. *Paper* Bimaterial interface hybrid element for piezoelectric laminated analysis, 97
LOHR, R. *Paper* Material properties from small specimens using the punch and bulge test, 423

MAJIMA, T. *Paper* Strain–concentration factor of circumferentially notched cylindrical bars under static tension, 347
MALL, S. *Paper* Methodology to analyse aerospace structures repaired with a bonded composite patch, 395
MONNO, G. *Technical Note* The design of hydrodynamically lubricated journal bearings against yield, 165
MOTTERSHEAD, J. E. *Paper* Material properties from small specimens using the punch and bulge test, 423

NABOULSI, S. *Paper* Methodology to analyse aerospace structures repaired with a bonded composite patch, 395
NADARAJAH, C. *Paper* Horizontal vessels on fixed supports used for storing high-temperature liquid: an experimental validation of finite element modelling, 83
NG, H. W. *Paper* Horizontal vessels on fixed supports used in strong

© IMechE 1999

high-temperature liquid: an experimental validation of finite element modelling, 83
NICOLETTO, G. *Paper* Accelerated life testing and thermomechanical simulation in power electronic device development, 455
NOWELL, D. *Paper* Strain changes caused by finite width slots, with particular reference to residual stress measurement, 285

OGLESBY, D. *Discussion* On E. Chicuzel, stress calculation in welds taking into account the bearing force between the welded parts, 369
ONG, L. S. *Paper* Horizontal vessels on fixed supports used for storing high-temperature liquid: an experimental validation of finite element modelling, 83

PATTERSON, E. A. *Technical Notes* Integration of spectral and phase-stepping methods in photoelasticity, 59. On the feasibility of determining discrete photoelastic parameters using the multi-load method, 295
PIPELZADEH, M. K. *Technical Note* Equivalent stress and total strain range predictions for multiaxial states of stress and strain, 53
PIRONDI, A. *Paper* Accelerated life testing and thermomechanical simulation in power electronic device development, 455

RIGHINIOTIS, T. D. *Papers* Stress intensity factors for a semi-elliptical surface crack in a T-shaped geometry. Part 1: tension and bending results, 147. Stress intensity factors for a semi-elliptical surface crack in a T-shaped geometry. Part 2: approximate solutions at the deepest point for arbitrary crack-face loading, 157
RITCHIE, S. J. K. *Papers* Non-uniform and dynamic torsion of elastic beams. Part 1: governing equations and particular solutions, 303. Non-uniform and dynamic torsion of elastic beams. Part 2: the double torsion test, 313
RODGERS, B. *Paper* Material properties from small specimens using the punch and bulge test, 423
ROSE, L. R. F. *Paper* A gradientless finite element procedure for shape optimization, 323
ROWLANDS, R. E. *Paper* Experimental determination of stress concentrations in orthotropic composites, 69

SACKFIELD, A. *Paper* A shrink-fit peg subject to bending and shearing forces, 23
SHIAH, Y. C. *Paper* Calculation of interior point stresses in two-dimensional boundary element analysis of anisotropic bodies with body forces, 117
SKOPINSKY, V. N. *Paper* Theoretical analysis of composite shell intersections, 107
SMART, J. *Papers* Crack growth in pin-loaded tubes. Part 1: numerical analysis, 253. Crack growth in pin-loaded tubes. Part 2: comparison of experimental data with numerical results, 271
STREKALOV, V. B. *Technical Note* Creep and relaxation of heritable orthotropic continua under the plane stress state, 361

TAN, C. L. *Paper* Calculation of interior point stresses in two-dimensional boundary element analysis of anisotropic bodies with body forces, 117
TOMLINSON, R. A. *Technical Note* On the feasibility of determining discrete photoelastic parameters using the multi-load method, 295
TOOTH, A. S. *Paper* Horizontal vessels on fixed supports used for storing high-temperature liquid: an experimental validation of finite element modelling, 83
TOVO, R. *Paper* Stress field parameters to predict the fatigue strength of notched components, 437

URRIOLAGOITIA SOSA, G. *Papers* A shrink-fit peg subject to bending and shearing forces, 23. Origins of partial slip in fretting—a review of known and potential solutions, 175

VICECONTI, M. *Paper* Towards the standardization of *in vitro* load transfer investigations of hip prostheses, 1
VILOTIC, D. *Paper* Disc upsetting between spherical dies and its application to the determination of forming limit curves, 17

WANG, Z. F. *Technical Note* Integration of spectral and phase-stepping methods in photoelasticity, 59
WARRIOR, N. A. *Paper* Advantages of cylindrical keys for torque transmission, 225
WEN, P. H. *Papers* Evaluation of the stress intensity factors for a three-dimensional interfacial crack by the boundary element method, 209. Dual boundary element methods for three-dimensional dynamic crack problems, 373
WHELAN, M. *Paper* Material properties from small specimens using the punch and bulge test, 423
WU, C.-C. *Paper* Bimaterial interface hybrid element for piezoelectric laminated analysis, 97

YOUNG, A. *Paper* Dual boundary element methods for three-dimensional dynamic crack problems, 373

© IMechE 1999

Subject Index

ACCELERATED LIFE TESTING AND THERMOMECHANICAL SIMULATION IN POWER ELECTRONIC DEVICE DEVELOPEMENT, *Paper*, 455
ADVANTAGES OF CYLINDRICAL KEYS FOR TORQUE TRANSMISSION, *Paper*, 225
A GRADIENTLESS FINITE ELEMENT PROCEDURE FOR SHAPE OPTIMIZATION, *Paper*, 323
Airbus A300, 413
Aircraft, commercial transport, 413
Airworthiness, structural, 413
Analysis:
  boundary element, 117
  of composite shell intersections, 107
  piezoelectric laminated, 97
AN EXPERIMENTAL AND FINITE ELEMENT STUDY OF THE NON-LINEAR FORCE–DISPLACEMENT CHARACTERISTICS OF TUBULAR YT-JOINTS UNDER COMBINED AXIAL LOADING, *Paper*, 183
Anisotropic bodies, 117
A QUADRATIC BOUNDARY ELEMENT FORMULATION FOR THREE-DIMENSIONAL CONTACT PROPLEMS WITH FRICTION, *Paper*, 235
A SHRINK-FIT PEG SUBJECT TO BENDING AND SHEARING FORCES, *Paper*, 23
AXIAL STIFFNESS AND TORSIONAL EFFECTS IN A 76 MM WIRE ROPE: EXPERIMENTAL DATA AND THEORETICAL PREDICTIONS, *Paper*, 39

Bars, notched cylindrical, 347
Beams, elastic, 303, 313
Bearings, hydrodynamically lubricated journal, 165
Bending, 147
BIMATERIAL INTERFACE HYBRID ELEMENT FOR PIEZOELECTRIC LAMINATED ANALYSIS, *Paper*, 97
Boundary element:
  analysis, 117
  dual, method, 373
  formulation, quadratic, 235
  method, 209

CALCULATION OF INTERIOR POINT STRESSES IN TWO-DIMENSIONAL BOUNDARY ELEMENT ANALYSIS OF ANISOTROPIC BODIES WITH BODY FORCES, *Paper*, 117
Components, notched, 437
Composites:
  bonded, patch, 395
  orthotropic, 69
  shell, 107
Contact, three-dimensional, 235
Continua, heritable orthotropic, 361
Crack:
  -face loading, 157
  growth, 253, 271
  semi-elliptical surface, 147, 157
  three-dimensional dynamic, 373
  three-dimensional interfacial, 209
CRACK GROWTH IN PIN-LOADED TUBES. PART 1: NUMERICAL ANALYSIS, *Paper*, 253
CRACK GROWTH IN PIN-LOADED TUBES. PART 2: COMPARISON OF EXPERIMENTAL DATA WITH NUMERICAL RESULTS, *Paper*, 271
Creep, 361
CREEP AND RELAXATION OF HERITABLE ORTHOTROPIC CONTINUA UNDER THE PLANE STRESS STATE, *Technical Note*, 361
Curves, limit, 17

Dies, spherical, 17
Disc upsetting, 17
DISC UPSETTING BETWEEN SPHERICAL DIES AND ITS APPLICATION TO THE DETERMINATION OF FORMING LIMIT CURVES, *Paper*, 17
Displacement, 183
DUAL BOUNDARY ELEMENT METHODS FOR THREE-DIMENSIONAL DYNAMIC CRACK PROBLEMS, *Paper*, 373

Element, bimaterial interface hybrid, 97
ENSURING THE CONTINUED STRUCTURAL AIRWORTHINESS OF THE AIRBUS A300 COMMERCIAL TRANSPORT AIRCRAFT, *Paper*, 413
EQUIVALENT STRESS AND TOTAL STRAIN RANGE PREDICTIONS FOR MULTIAXIAL STATES OF STRESS AND STRAIN, *Technical Note*, 53
EVALUATION OF THE STRESS INTENSITY FACTORS FOR A THREE-DIMENSIONAL INTERFACIAL CRACK BY THE BOUNDARY ELEMENT METHOD, *Paper*, 209
EXPERIMENTAL DETERMINATION OF STRESS CONCENTRATIONS IN ORTHOTROPIC COMPOSITES, *Paper*, 69

Fatigue strength, 431
Film, 337
FILM DATA REDUCTION FROM TAYLOR IMPACT TESTS, *Paper*, 337
Finite element:
  method, 31
  modelling, 83, 129
  procedure, gradientless, 323
  study, 183
FINITE ELEMENT MODELLING OF LOCAL CONTACT CONDITIONS IN GEAR TEETH, *Paper*, 129
Force(s):
  bending, 23
  body, 117
  non-linear, 183
  shearing, 23
Fretting, 175
Friction, 235

Gear teeth, 129
Geometry, T-shaped, 147, 157

HORIZONTAL VESSELS ON FIXED SUPPORTS USED FOR STORING HIGH-TEMPERATURE LIQUID: AN EXPERIMENTAL VALIDATION OF FINITE ELEMENT MODELLING, *Paper*, 83
Hydrodynamically lubricated journal bearings, 165

IDENTIFICATION AND MEASUREMENT OF DUCTILE DAMAGE PARAMETERS, *Paper*, 463
INTEGRATION OF SPECTRAL AND PHASE-STEPPING METHODS IN PHOTOELASTICITY, *Technical Note*, 59

Joints, tubular YT-, 183

Keys, cylindrical, 225

Liquid, high-temperature, 83
Loading:
  arbitrary crack-face, 157
  combined axial, 183
Load transfer, *in vitro*, 1

MATERIAL PROPERTIES FROM SMALL SPECIMENS USING THE PUNCH AND BULGE TEST, *Paper*, 423
Method:
  boundary element, 209
  dual boundary element, 373
  finite element, 31
  multi-load, 295
  phase-stepping, 59
  spectral, 59
METHODOLOGY TO ANALYSE AEROSPACE STRUCTURES REPAIRED WITH A BONDED COMPOSITE PATCH, *Paper*, 395
Modelling:
  boundary element, 129
  finite element, 83

© IMechE 1999

NON-UNIFORM AND DYNAMIC TORSION OF ELASTIC BEAMS. PART 1: GOVERNING EQUATIONS AND PARTICULAR SOLUTIONS, *Paper*, 303
NON-UNIFORM AND DYNAMIC TORSION OF ELASTIC BEAMS. PART 2: THE DOUBLE TORSION TEST, *Paper*, 313

ON THE FEASIBILITY OF DETERMINING DISCRETE PHOTOELASTIC PARAMETERS USING THE MULTI-LOAD METHOD, *Technical Note*, 295
Optimization, shape, 323
ORIGINS OF PARTIAL SLIP IN FRETTING—A REVIEW OF KNOWN AND POTENTIAL SOLUTIONS, *Paper*, 175

Parameters:
  ductile damage, 463
  photoelastic, 295
Patch, bonded composite, 395
Peg, shrink-fit, 23
Photoelasticity, 59
Photoelastic parameters, 295
Piezoelectric laminated analysis, 97
Power electronic device, 455
Pressure, uniform, 217
Prostheses, hip, 1

Quadratic boundary element formulation, 235

Ring, confocal elliptic, 217

Shape optimization, 323
Slip, partial, 175
Slots, finite width, 285
Stiffness, axial, 39
Strain, 53, 285
  –concentration factor, 347
  multiaxial states of, 53
  range, 53
STRAIN CHANGES CAUSED BY FINITE WIDTH SLOTS, WITH PARTICULAR REFERENCE TO RESIDUAL STRESS MEASUREMENT, *Paper*, 285
STRAIN–CONCENTRATION FACTOR OF CIRCUMFERENTIALLY NOTCHED CYLINDRICAL BARS UNDER STATIC TENSION, *Paper*, 347
Stress, 53, 217
  concentrations, 69
  equivalent, 53
  field parameters, 437
  intensity factors, 147, 157, 209
  interior point, 117
  multiaxial states of, 53
  plane, 361
  residual, 285
STRESSES IN A CONFOCAL ELLIPTIC RING SUBJECT TO UNIFORM PRESSURE, *Technical Note*, 217
STRESS FIELD PARAMETERS TO PREDICT THE FATIGUE STRENGTH OF NOTCHED COMPONENTS, *Paper*, 437
STRESS INTENSITY FACTORS FOR A SEMI-ELLIPTICAL SURFACE CRACK IN A T-SHAPED GEOMETRY. PART 1: TENSION AND BENDING RESULTS, *Paper*, 147
STRESS INTENSITY FACTORS FOR A SEMI-ELLIPTICAL SURFACE CRACK IN A T-SHAPED GEOMETRY. PART 2: APPROXIMATE SOLUTIONS AT THE DEEPEST POINT FOR ARBITRARY CRACK-FACE LOADING, *Paper*, 157
Structures, aerospace, 395
Study, finite element, 183
Supports, fixed, 83

Taylor impact tests, 337
Tension, 147
  static, 347
Termination effects, 31
Test(s):
  double torsion, 313
  punch and bulge, 423
  Taylor impact, 337
THE ANALYSIS OF TERMINATION EFFECTS IN WIRE STRAND USING THE FINITE ELEMENT METHOD, *Paper*, 31
THE DESIGN OF HYDRODYNAMICALLY LUBRICATED JOURNAL BEARINGS AGAINST YIELD, *Technical Note*, 165
THEORETICAL ANALYSIS OF COMPOSITE SHELL INTERSECTIONS, *Paper*, 107
Thermomechanical simulation, 455
Torque, 225
Torsion:
  double, test, 313
  dynamic, 303, 313
  non-uniform, 303, 313
Torsional effects, 39
TOWARDS THE STANDARDIZATION OF *IN VITRO* LOAD TRANSFER INVESTIGATIONS OF HIP PROSTHESES, *Paper*, 1
Transmission, torque, 225
Tubes, pin-loaded, 253, 271

Vessels, horizontal, 83

Wire:
  rope, 39
  strand, 31

Yield, 165

© IMechE 1999